

# MAGNUM™ EXM



## MAX FLOW

5000 GPM

## LIGHTWEIGHT

115 LBS

## COMPACT

19" Stow Height

## EFFICIENT

38 PSI total static pressure drop

At only 115 lbs (52kg), the 6" inlet and dual waterway design of the Magnum EXM produces 5000 GPM (19,000 LPM) with just 38 PSI (2.6 bar) of total static pressure drop. The efficient waterway results in a lower inlet pressure requirement while still producing a reach of over 400 feet (120 meters).

# MAGNUM™ EXM

## EXM DESIGN FEATURES

- Heavy-duty swivel joints supported by thrust rods and bearings
- Efficient elliptical waterway
- Hard anodized aluminum alloy construction
- High torque motors

## EXM TECHNOLOGY BENEFITS

- Wired or wireless operator control
- Programmable travel limits (stow, keep-out zones and oscillate)
- Absolute position sensors for precise monitor control
- CANbus J1939 for total system communication



### SPECIFICATIONS

<b>Model</b>	7600
<b>Max Flow</b>	5000 GPM (19,000 LPM)
<b>Max Pressure</b>	200 PSI (13.8 BAR)
<b>Inlet</b>	6" 150# Flange
<b>Outlet</b>	6" NHT
<b>Vertical Travel</b>	-60° to +90°
<b>Horizontal Travel</b>	L175° to R175°
<b>Control Communication</b>	CAN bus J1939 2.4 Ghz digital radio frequency (unlicensed)
<b>Material</b>	Teflon impregnated, hard anodized Elk-O-Lite®
<b>Swing Radius</b>	13"
<b>Stow Height</b>	19"
<b>Weight</b>	115 lbs. (52kg) including nozzle