

FORESTRY & WILDLAND

Not your "throw away" type nozzles, our rugged wildland products are built to perform season-after-season for your engine crew. They are built of lightweight aluminum, and the pattern can be selected with a quick action twist.

MYSTERY

TWIST SHUTOFF TIPS

The Mystery® Nozzle incorporates a twist-type shutoff, opening in straight stream and producing a variable flow from straight stream to wide fog with low pressure options available. Paired with an XD™ shutoff, the Mystery nozzle tip offers an extremely convenient method of advancing hose lines, particularly in the wildland / urban interface in progressive hose lay operations. Simply close the shutoff, remove the Mystery tip, attach additional hose, and then reattach the tip at the end of the line. The tip's built-in shutoff allows for the line to be advanced rapidly without the need for an additional nozzle.



L-205-BA 1.5" Rigid Inlet

Flow Rates:

125 gpm @ 75 psi
(475 LPM @ 5 BAR)

60 gpm @ 100 psi
(230 LPM @ 7 BAR)

95 gpm @ 100 psi
(360 LPM @ 7 BAR)

125 gpm @ 100 psi
(475 LPM @ 7 BAR)



PAIRS WITH MID-LOW XD SHUTOFF



ST-180-XD-F

- 1.5" Inlet / 6.5" (165mm) Length
- Available discharge sizes: 1/2" and 3/8"



XD-205-BAF 1.5" Rigid Inlet

- Dual flow nozzle design
- 30 gpm & 80 gpm @ 75 psi (115 LPM & 300 LPM @ 5 BAR)
- High visibility reflective striping

S-205-BAF 1.0" or 0.75" GHT Rigid Inlet

- Available in 12 gpm (45 LPM) or 23 gpm (90 LPM) single flow settings
- Twist shut-off
- For use with pressures up to 600 psi (40 BAR)



205-BA 1.5" Rigid Inlet

Flow Rates:

200 gpm @ 50 psi (750 LPM @ 3.5 BAR)	125 gpm @ 75 psi (475 LPM @ 5 BAR)	170 gpm @ 100 psi (640 LPM @ 7 BAR)
	200 gpm @ 75 psi (750 LPM @ 5 BAR)	250 gpm @ 100 psi (950 LPM @ 7 BAR)



D-205-BA 2.5" Rigid Inlet

Flow Rates:

200 gpm @ 50 psi (750 LPM @ 3.5 BAR)	125 gpm @ 75 psi (475 LPM @ 5 BAR)	170 gpm @ 100 psi (640 LPM @ 7 BAR)
	200 gpm @ 75 psi (750 LPM @ 5 BAR)	250 gpm @ 100 psi (950 LPM @ 7 BAR)